

19.11.2021

### Kit Components

| Product code                                                     | Description                                        |
|------------------------------------------------------------------|----------------------------------------------------|
| <b>000051</b><br><b>000052</b><br><b>000055</b><br><b>000098</b> | <b>MOTIP Polyester Putty - with hardener - SET</b> |

Components:

|         |                       |
|---------|-----------------------|
| 000051S | MOTIP Polyester Putty |
| 80692   | Hardener Paste        |

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 6 (replaces version 5)

Revision: 19.11.2021

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1 Product identifier

Trade name: **MOTIP Polyester Putty**

Article number: 000051S, 000052S, 000055S, 000098S, 496510Salt, 496527Salt, 496534Salt, 496541Salt

##### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

##### Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

##### Product category

Hardener

##### Process category

PROC10 Roller application or brushing

##### Application of the substance / the mixture

Knife filler/ Surfacers

##### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

European Aerosols GmbH\*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

\*Formerly known as Motip Dupli GmbH

##### Further information obtainable from:

Department Product Safety

##### 1.4 Emergency telephone number:

Tel.: +49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergency phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if child has been poisoned: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

#### SECTION 2: Hazards identification

##### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 2)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 6 (replaces version 5)

Revision: 19.11.2021

**Trade name: MOTIP Polyester Putty**

(Contd. of page 1)



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### Hazard pictograms



GHS02



GHS07



GHS08

#### Signal word Danger

#### Hazard-determining components of labelling:

styrene

#### Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection.

P314 Get medical advice/attention if you feel unwell.

P405 Store locked up.

P501 Dispose of contents / container in accordance with regional regulations.

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

#### Dangerous components:

|                                                                                                    |                                                                                                                                                                                                |           |
|----------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| CAS: 100-42-5<br>EINECS: 202-851-5<br>Index number: 601-026-00-0<br>Reg.nr.: 01-2119457861-32-xxxx | styrene<br>Flam. Liq. 3, H226<br>Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304<br>Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335<br>Aquatic Chronic 3, H412 | 10-<12.5% |
| CAS: 7727-43-7<br>EINECS: 231-784-4<br>Reg.nr.: 01-2119491274-35                                   | barium sulphate, natural<br>substance with a Community workplace exposure limit                                                                                                                | 5-<10%    |

(Contd. on page 3)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 6 (replaces version 5)

Revision: 19.11.2021

**Trade name: MOTIP Polyester Putty**

(Contd. of page 2)

**· Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.  
For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**· 4.1 Description of first aid measures****· General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**· After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

**· 5.1 Extinguishing media****· Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

**· 5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

No further relevant information available.

**· 5.3 Advice for firefighters -**

· **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

**· 6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

**· 6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

**· 6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.

**· Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 6 (replaces version 5)

Revision: 19.11.2021

**Trade name: MOTIP Polyester Putty**

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

##### · **Ingredients with limit values that require monitoring at the workplace:**

###### **100-42-5 styrene**

|     |                                                    |
|-----|----------------------------------------------------|
| WEL | Short-term value: 1080 mg/m <sup>3</sup> , 250 ppm |
|     | Long-term value: 430 mg/m <sup>3</sup> , 100 ppm   |

###### **7727-43-7 barium sulphate, natural**

|     |                                            |
|-----|--------------------------------------------|
| WEL | Long-term value: 10* 4** mg/m <sup>3</sup> |
|     | *inhalable dust **respirable dust          |

- **Additional information:** The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**

##### · **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing  
 Wash hands before breaks and at the end of work.  
 Store protective clothing separately.  
 Avoid contact with the eyes and skin.  
 Avoid contact with the eyes.

##### · **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

##### · **Hand protection**



Protective gloves

##### · **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

##### · **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 6 (replaces version 5)

Revision: 19.11.2021

**Trade name: MOTIP Polyester Putty**

(Contd. of page 4)

· Eye/face protection



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

|                                                            |                                              |
|------------------------------------------------------------|----------------------------------------------|
| · Physical state                                           | Fluid                                        |
| · Colour:                                                  | Grey                                         |
| · Odour:                                                   | Characteristic                               |
| · Odour threshold:                                         | Not determined.                              |
| · Melting point/freezing point:                            | Undetermined.                                |
| · Boiling point or initial boiling point and boiling range | 145 °C (293 °F)                              |
| · Flammability                                             | Not applicable.                              |
| · Lower and upper explosion limit                          |                                              |
| · Lower:                                                   | 1.2 Vol %                                    |
| · Upper:                                                   | 8.9 Vol %                                    |
| · Flash point:                                             | 31 °C (87.8 °F)                              |
| · Decomposition temperature:                               | Not determined.                              |
| · pH                                                       | Mixture is non-soluble (in water).           |
| · Viscosity:                                               |                                              |
| · Kinematic viscosity                                      | Not determined.                              |
| · Dynamic:                                                 | Not determined.                              |
| · Solubility                                               |                                              |
| · water:                                                   | Not miscible or difficult to mix.            |
| · Partition coefficient n-octanol/water (log value)        | Not determined.                              |
| · Vapour pressure at 20 °C (68 °F):                        | 6 hPa (4.5 mm Hg)                            |
| · Density and/or relative density                          |                                              |
| · Density at 20 °C (68 °F):                                | 0.7-1.9 g/cm <sup>3</sup> (5.8-15.9 lbs/gal) |
| · Relative density                                         | Not determined.                              |
| · Vapour density                                           | Not determined.                              |

#### · 9.2 Other information

|                                                                                 |                                                                                             |
|---------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| · Appearance:                                                                   |                                                                                             |
| · Form:                                                                         | Pasty                                                                                       |
| · Important information on protection of health and environment, and on safety. |                                                                                             |
| · Ignition temperature:                                                         | 480 °C (896 °F)                                                                             |
| · Explosive properties:                                                         | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Solvent content:                                                              |                                                                                             |
| · Organic solvents:                                                             | 0.3 %                                                                                       |
| · VOC (EC)                                                                      | ---                                                                                         |
|                                                                                 | 90-230 g/l                                                                                  |
| · VOC-EU%                                                                       | 12.00 %                                                                                     |
| · Solids content:                                                               | 88.0 %                                                                                      |
| · Change in condition                                                           |                                                                                             |
| · Evaporation rate                                                              | Not determined.                                                                             |

#### · Information with regard to physical hazard classes

|                   |      |
|-------------------|------|
| · Explosives      | Void |
| · Flammable gases | Void |
| · Aerosols        | Void |

(Contd. on page 6)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 6 (replaces version 5)

Revision: 19.11.2021

**Trade name: MOTIP Polyester Putty**

(Contd. of page 5)

|                                                                                    |                              |
|------------------------------------------------------------------------------------|------------------------------|
| · <b>Oxidising gases</b>                                                           | Void                         |
| · <b>Gases under pressure</b>                                                      | Void                         |
| · <b>Flammable liquids</b>                                                         | Flammable liquid and vapour. |
| · <b>Flammable solids</b>                                                          | Void                         |
| · <b>Self-reactive substances and mixtures</b>                                     | Void                         |
| · <b>Pyrophoric liquids</b>                                                        | Void                         |
| · <b>Pyrophoric solids</b>                                                         | Void                         |
| · <b>Self-heating substances and mixtures</b>                                      | Void                         |
| · <b>Substances and mixtures, which emit flammable gases in contact with water</b> | Void                         |
| · <b>Oxidising liquids</b>                                                         | Void                         |
| · <b>Oxidising solids</b>                                                          | Void                         |
| · <b>Organic peroxides</b>                                                         | Void                         |
| · <b>Corrosive to metals</b>                                                       | Void                         |
| · <b>Desensitised explosives</b>                                                   | Void                         |

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

#### 100-42-5 styrene

|            |           |                              |
|------------|-----------|------------------------------|
| Oral       | LD50      | 5000 mg/kg (rat)             |
| Dermal     | LD50      | >2000 mg/kg (rat) (OECD 402) |
| Inhalative | LC50 / 4h | 11.8 mg/l (rat)              |

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Reproductive toxicity** Suspected of damaging the unborn child.
- **STOT-repeated exposure** Causes damage to the hearing organs through prolonged or repeated exposure.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 6 (replaces version 5)

Revision: 19.11.2021

**Trade name: MOTIP Polyester Putty**

(Contd. of page 6)

- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**  
Disposal must be made according to official regulations.  
Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |                                                                                                                                                                                                                             |                                                                                                                              |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>· <b>14.1 UN number or ID number</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>                                                                                                    | <p style="text-align: center;">UN3269</p>                                                                                    |
| <ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG, IATA</b></li> </ul>                                                                                  | <p style="text-align: center;">3269 POLYESTER RESIN KIT<br/>POLYESTER RESIN KIT</p>                                          |
| <ul style="list-style-type: none"> <li>· <b>14.3 Transport hazard class(es)</b></li> <li>· <b>ADR</b></li> </ul>                                                                                                            | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>                                                                                                                                    | <p style="text-align: center;">3 (F3) Flammable liquids.<br/>3</p>                                                           |
| <ul style="list-style-type: none"> <li>· <b>IMDG, IATA</b></li> </ul>                                                                                                                                                       | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>                                                                                                                                    | <p style="text-align: center;">3 Flammable liquids.<br/>3</p>                                                                |
| <ul style="list-style-type: none"> <li>· <b>14.4 Packing group</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>                                                                                                             | <p style="text-align: center;">III</p>                                                                                       |
| <ul style="list-style-type: none"> <li>· <b>14.5 Environmental hazards:</b></li> </ul>                                                                                                                                      | <p style="text-align: center;">Not applicable.</p>                                                                           |
| <ul style="list-style-type: none"> <li>· <b>14.6 Special precautions for user</b></li> <li>· <b>Hazard identification number (Kemler code):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Category</b></li> </ul> | <p style="text-align: center;">Warning: Flammable liquids.<br/>-<br/>F-E,S-D<br/>A</p>                                       |

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 6 (replaces version 5)

Revision: 19.11.2021

**Trade name: MOTIP Polyester Putty**

(Contd. of page 7)

|                                                                       |                                                |
|-----------------------------------------------------------------------|------------------------------------------------|
| · <b>14.7 Maritime transport in bulk according to IMO instruments</b> | Not applicable.                                |
| · <b>Transport/Additional information:</b>                            |                                                |
| · <b>ADR</b>                                                          |                                                |
| · <b>Limited quantities (LQ)</b>                                      | 5L                                             |
| · <b>Excepted quantities (EQ)</b>                                     | Code: E0<br>Not permitted as Excepted Quantity |
| · <b>Transport category</b>                                           | 3                                              |
| · <b>Tunnel restriction code</b>                                      | E                                              |
| · <b>IMDG</b>                                                         |                                                |
| · <b>Limited quantities (LQ)</b>                                      | 5L                                             |
| · <b>Excepted quantities (EQ)</b>                                     | Code: See SP340                                |
| · <b>UN "Model Regulation":</b>                                       | UN 3269 POLYESTER RESIN KIT, 3, III            |

\*

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c** FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50000 t
- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57**
- None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

\*

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- **Abbreviations and acronyms:**
- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)

GB

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 19.11.2021

Version number 6 (replaces version 5)

Revision: 19.11.2021

**Trade name: MOTIP Polyester Putty**

(Contd. of page 8)

*CAS: Chemical Abstracts Service (division of the American Chemical Society)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**SVHC: Substances of Very High Concern**vPvB: very Persistent and very Bioaccumulative**Flam. Liq. 3: Flammable liquids – Category 3**Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Repr. 2: Reproductive toxicity – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3***· \* Data compared to the previous version altered.**

GB

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 15 (replaces version 14)

Revision: 21.09.2021

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: **Hardener Paste**

### Article number:

80692, 80694, 80695, 80702, 80703, 80704, 80705, 80706, 80707, 80711, 80716, 80719, 80726, 80753, 81255, 81275, 81276, 85302, 360268, 499191, 499603, 600078, 600160, 600177, 600269, 600276, 784866, 80267alt, 80400alt, 80691alt, 80693alt, 80696alt, 80697alt, 80698alt, 80699alt, 80700alt, 80701alt, 80708alt, 80709alt, 80710alt, 80712alt, 80728alt, 80754alt

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

### Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9b Fillers, putties, plasters, modelling clay

Process category PROC10 Roller application or brushing

Application of the substance / the mixture Hardening agent/ Curing agent

### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

European Aerosols GmbH\*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

\*Formerly known as Motip Dupli GmbH

Further information obtainable from: Department Product Safety

### 1.4 Emergency telephone number:

Tel.: +49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergency phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if child has been poisoned: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Org. Perox. E

H242 Heating may cause a fire.

(Contd. on page 2)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 15 (replaces version 14)

Revision: 21.09.2021

**Trade name: Hardener Paste**

(Contd. of page 1)



environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### Hazard pictograms



GHS02



GHS07



GHS09

#### Signal word Warning

#### Hazard-determining components of labelling:

dibenzoyl peroxide

#### Hazard statements

H242 Heating may cause a fire.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents / container in accordance with regional regulations.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

#### Dangerous components:

|                            |                                                              |         |
|----------------------------|--------------------------------------------------------------|---------|
| CAS: 94-36-0               | dibenzoyl peroxide                                           | 25-<50% |
| EINECS: 202-327-6          | Org. Perox. B, H241                                          |         |
| Index number: 617-008-00-0 | Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10) |         |
| Reg.nr.: 01-2119511472-50  | Eye Irrit. 2, H319; Skin Sens. 1, H317                       |         |

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 15 (replaces version 14)

Revision: 21.09.2021

**Trade name: Hardener Paste**

(Contd. of page 2)

|                                                                  |                                                                           |         |
|------------------------------------------------------------------|---------------------------------------------------------------------------|---------|
| CAS: 131-11-3<br>EINECS: 205-011-6<br>Reg.nr.: 01-2119437229-36  | dimethyl phthalate<br>substance with a Community workplace exposure limit | 25-<50% |
| CAS: 107-21-1<br>EINECS: 203-473-3<br>Index number: 603-027-00-1 | ethanediol<br>⚠ Acute Tox. 4, H302                                        | 5-<10%  |

• **Additional information:** For the wording of the listed hazard phrases refer to section 16.

\*

### SECTION 4: First aid measures

#### • 4.1 Description of first aid measures

##### • After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

##### • After skin contact: Immediately wash with water and soap and rinse thoroughly.

##### • After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

##### • After swallowing:

Seek immediate medical advice.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

#### • 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

#### • 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

\*

### SECTION 5: Firefighting measures

#### • 5.1 Extinguishing media

#### • Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

#### • 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

No further relevant information available.

#### • 5.3 Advice for firefighters -

#### • Protective equipment: No special measures required.

\*

### SECTION 6: Accidental release measures

#### • 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

#### • 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

#### • 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

#### • 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

\*

### SECTION 7: Handling and storage

#### • 7.1 Precautions for safe handling No special measures required.

(Contd. on page 4)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 15 (replaces version 14)

Revision: 21.09.2021

**Trade name: Hardener Paste**

(Contd. of page 3)

- **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:**  
Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 5.2
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

##### 131-11-3 dimethyl phthalate

WEL Short-term value: 10 mg/m<sup>3</sup>  
Long-term value: 5 mg/m<sup>3</sup>

##### 107-21-1 ethanediol

WEL Short-term value: 104\*\* mg/m<sup>3</sup>, 40\*\* ppm  
Long-term value: 10\* 52\*\* mg/m<sup>3</sup>, 20\*\* ppm  
Sk \*particulate \*\*vapour

- **Additional information:** The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.  
Avoid contact with the eyes.
- **Respiratory protection:** Not necessary if room is well-ventilated.
- **Hand protection**



Protective gloves

#### · **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

#### · **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

(Contd. on page 5)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 15 (replaces version 14)

Revision: 21.09.2021

**Trade name: Hardener Paste**

(Contd. of page 4)

· **Eye/face protection**

Tightly sealed goggles

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

|                                                            |                                                                                     |
|------------------------------------------------------------|-------------------------------------------------------------------------------------|
| · Physical state                                           | Fluid                                                                               |
| · Colour:                                                  | Pink                                                                                |
| · Odour:                                                   | Characteristic                                                                      |
| · Odour threshold:                                         | Not determined.                                                                     |
| · Melting point/freezing point:                            | Undetermined.                                                                       |
| · Boiling point or initial boiling point and boiling range | 100 °C (212 °F) (7732-18-5 water, distilled, conductivity or of similar purity)     |
| · Flammability                                             | Not applicable.                                                                     |
| · Lower and upper explosion limit                          |                                                                                     |
| · Lower:                                                   | Not determined.                                                                     |
| · Upper:                                                   | Not determined.                                                                     |
| · Flash point:                                             | Not applicable.                                                                     |
| · Decomposition temperature:                               | 50 °C (122 °F) (SADT)                                                               |
| · pH at 20 °C (68 °F)                                      | 7                                                                                   |
| · Viscosity:                                               |                                                                                     |
| · Kinematic viscosity                                      | Not determined.                                                                     |
| · Dynamic:                                                 | Not determined.                                                                     |
| · Solubility                                               |                                                                                     |
| · water:                                                   | Not miscible or difficult to mix.                                                   |
| · Partition coefficient n-octanol/water (log value)        | Not determined.                                                                     |
| · Vapour pressure at 20 °C (68 °F):                        | 23 hPa (17.3 mm Hg) (7732-18-5 water, distilled, conductivity or of similar purity) |
| · Density and/or relative density                          |                                                                                     |
| · Density at 20 °C (68 °F):                                | 1.1 g/cm <sup>3</sup> (9.2 lbs/gal)                                                 |
| · Relative density                                         | Not determined.                                                                     |
| · Vapour density                                           | Not determined.                                                                     |

#### · 9.2 Other information

|                                                                                 |                                               |
|---------------------------------------------------------------------------------|-----------------------------------------------|
| · Appearance:                                                                   |                                               |
| · Form:                                                                         | Pasty                                         |
| · Important information on protection of health and environment, and on safety. |                                               |
| · Ignition temperature:                                                         | 410 °C (770 °F)                               |
| · Explosive properties:                                                         | Product does not present an explosion hazard. |
| · Solvent content:                                                              |                                               |
| · Organic solvents:                                                             | 9.0 %                                         |
| · Water:                                                                        | 11.0 %                                        |
| · VOC (EC)                                                                      | -- %                                          |
|                                                                                 | ---                                           |
|                                                                                 | 112.6 g/l                                     |
| · VOC-EU%                                                                       | 9.00 %                                        |
| · Solids content:                                                               | 55.0 %                                        |
| · Change in condition                                                           |                                               |
| · Evaporation rate                                                              | Not determined.                               |

(Contd. on page 6)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 15 (replaces version 14)

Revision: 21.09.2021

**Trade name: Hardener Paste**

(Contd. of page 5)

|                                                                                    |                           |
|------------------------------------------------------------------------------------|---------------------------|
| · <b>Information with regard to physical hazard classes</b>                        |                           |
| · <b>Explosives</b>                                                                | Void                      |
| · <b>Flammable gases</b>                                                           | Void                      |
| · <b>Aerosols</b>                                                                  | Void                      |
| · <b>Oxidising gases</b>                                                           | Void                      |
| · <b>Gases under pressure</b>                                                      | Void                      |
| · <b>Flammable liquids</b>                                                         | Void                      |
| · <b>Flammable solids</b>                                                          | Void                      |
| · <b>Self-reactive substances and mixtures</b>                                     | Void                      |
| · <b>Pyrophoric liquids</b>                                                        | Void                      |
| · <b>Pyrophoric solids</b>                                                         | Void                      |
| · <b>Self-heating substances and mixtures</b>                                      | Void                      |
| · <b>Substances and mixtures, which emit flammable gases in contact with water</b> | Void                      |
| · <b>Oxidising liquids</b>                                                         | Void                      |
| · <b>Oxidising solids</b>                                                          | Void                      |
| · <b>Organic peroxides</b>                                                         | Heating may cause a fire. |
| · <b>Corrosive to metals</b>                                                       | Void                      |
| · <b>Desensitised explosives</b>                                                   | Void                      |

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** To avoid thermal decomposition do not overheat.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **11.2 Information on other hazards**

#### · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
- The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Very toxic for fish

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 15 (replaces version 14)

Revision: 21.09.2021

**Trade name: Hardener Paste**

(Contd. of page 6)

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
 Do not allow product to reach ground water, water course or sewage system.  
 Danger to drinking water if even small quantities leak into the ground.  
 Also poisonous for fish and plankton in water bodies.  
 Very toxic for aquatic organisms

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packaging:**

- **Recommendation:**

Disposal must be made according to official regulations.  
 Disposal must be made according to official regulations.

### SECTION 14: Transport information

- **14.1 UN number or ID number**

- **ADR, IMDG, IATA**

UN3108

- **14.2 UN proper shipping name**

- **ADR**

3108 ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide), ENVIRONMENTALLY HAZARDOUS  
 ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)

- **IMDG, IATA**

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class**

5.2 (P1) Organic peroxides.

- **Label**

5.2

- **IMDG, IATA**



- **Class**

5.2 Organic peroxides.

- **Label**

5.2

- **14.4 Packing group**

- **ADR, IMDG, IATA**

not regulated

- **14.5 Environmental hazards:**

- **Marine pollutant:**

Yes

- **Special marking (ADR):**

Symbol (fish and tree)

- **14.6 Special precautions for user**

Warning: Organic peroxides.

- **Hazard identification number (Kemler code):**

-

- **EMS Number:**

F-J,S-R

- **Stowage Category**

D

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 15 (replaces version 14)

Revision: 21.09.2021

**Trade name: Hardener Paste**

(Contd. of page 7)

|                                                                       |                                                                                                           |
|-----------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| · <b>Stowage Code</b>                                                 | SW1 Protected from sources of heat.                                                                       |
| · <b>Segregation Code</b>                                             | SG35 Stow "separated from" SGG1-acids<br>SG36 Stow "separated from" SGG18-alkalis.<br>SG72 See 7.2.6.3.2. |
| · <b>14.7 Maritime transport in bulk according to IMO instruments</b> | Not applicable.                                                                                           |
| · <b>Transport/Additional information:</b>                            |                                                                                                           |
| · <b>ADR</b>                                                          |                                                                                                           |
| · <b>Limited quantities (LQ)</b>                                      | 500 g                                                                                                     |
| · <b>Excepted quantities (EQ)</b>                                     | Code: E0<br>Not permitted as Excepted Quantity                                                            |
| · <b>Transport category</b>                                           | 2                                                                                                         |
| · <b>Tunnel restriction code</b>                                      | D                                                                                                         |
| · <b>IMDG</b>                                                         |                                                                                                           |
| · <b>Limited quantities (LQ)</b>                                      | 500 g                                                                                                     |
| · <b>Excepted quantities (EQ)</b>                                     | Code: E0<br>Not permitted as Excepted Quantity                                                            |
| · <b>UN "Model Regulation":</b>                                       | UN 3108 ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE), 5.2, ENVIRONMENTALLY HAZARDOUS               |

\*

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES  
E1 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t
- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

\*

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H241 Heating may cause a fire or explosion.  
H302 Harmful if swallowed.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.
- **Abbreviations and acronyms:**  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

(Contd. on page 9)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 19.11.2021

Version number 15 (replaces version 14)

Revision: 21.09.2021

**Trade name: Hardener Paste**

(Contd. of page 8)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Org. Perox. B: Organic peroxides – Type B

Org. Perox. E: Organic peroxides – Type E/F

Acute Tox. 4: Acute toxicity – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

· **\* Data compared to the previous version altered.**

GB