

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.01.2022 Version number 9 (replaces version 8) Revision: 12.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Motip Hardener
- · Article number:

000079, 000075alt, 000077alt, 000078alt, 000153alt, 496718alt, 496701alt, 894923alt, 894930alt

- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9b Fillers, putties, plasters, modelling clay
- · Process category PROC10 Roller application or brushing
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

European Aerosols GmbH*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

- *Formerly known as Motip Dupli GmbH
- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

Tel.:+49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergeny phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if childs have been poisened: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Org. Perox. E H242 Heating may cause a fire.



Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Version number 9 (replaces version 8) Printing date 12.01.2022 Revision: 12.01.2022

Trade name: Motip Hardener

(Contd. of page 1)



Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

· Signal word Warning

· Hazard-determining components of labelling:

dibenzoyl peroxide

· Hazard statements

H242 Heating may cause a fire.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves / eye protection. P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Store in a well-ventilated place. Keep cool.

P501 Dispose of contents / container in accordance with regional regulations.

· 2.3 Other hazards

P403+P235

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 94-36-0	dibenzoyl peroxide	25-<50%
EINECS: 202-327-6	🔗 🕲 Org. Perox. B, H241	1
Index number: 617-008-00-0	Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410	
Reg.nr.: 01-2119511472-50	(M=10)	
	♠ Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 131-11-3	dimethyl phthalate	25-<50%
EINECS: 205-011-6	substance with a Community workplace exposure limit	
Reg.nr.: 01-2119437229-36		
CAS: 107-21-1	ethanediol	5-<10%
EINECS: 203-473-3	1 Acute Tox. 4, H302	1
Index number: 603-027-00-1		
	(Co	ntd. on page 3)

Printing date 12.01.2022 Version number 9 (replaces version 8) Revision: 12.01.2022

Trade name: Motip Hardener

(Contd. of page 2)

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

No further relevant information available.

- · 5.3 Advice for firefighters -
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special measures required.
- · Information about fire and explosion protection: Keep ignition sources away Do not smoke.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility:

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

(Contd. on page 4)

Printing date 12.01.2022 Version number 9 (replaces version 8) Revision: 12.01.2022

Trade name: Motip Hardener

(Contd. of page 3)

- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 5.2
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

131-11-3 dimethyl phthalate

WEL Short-term value: 10 mg/m³ Long-term value: 5 mg/m³

107-21-1 ethanediol

WEL Short-term value: 104** mg/m³, 40** ppm Long-term value: 10* 52** mg/m³, 20** ppm Sk *particulate **vapour

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Hand protection



Protective gloves

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye/face protection



Tightly sealed goggles

GB

Printing date 12.01.2022 *Version number 9 (replaces version 8)* Revision: 12.01.2022

Trade name: Motip Hardener

(Contd. of page 4)

SECTION 9: Phys	ical and c	hemical p	broperties
-----------------	------------	-----------	------------

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: Pink

· Odour: Characteristic · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

100 °C (212 °F) (7732-18-5 water, distilled,

conductivity or of similar purity)

· Flammability Not applicable.

· Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined. · Flash point: Not applicable. · Decomposition temperature: 50 °C (122 °F) (SADT)

· pH at 20 °C (68 °F)

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic: Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 $^{\circ}C$ (68 $^{\circ}F$): 23 hPa (17.3 mm Hg) (7732-18-5 water, distilled,

conductivity or of similar purity)

· Density and/or relative density

· Density at 20 °C (68 °F): $1.1 \text{ g/cm}^3 (9.2 \text{ lbs/gal})$ · Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Pasty

· Important information on protection of health and

environment, and on safety.

410 °C (770 °F) · Ignition temperature:

· Explosive properties: Product does not present an explosion hazard.

· Solvent content:

9.0 % · Organic solvents: · Water: 11.0 % · **VOC** (**EC**) -- %

 $112.6 \, g/l$ 9.00 %

· VOC-EU% · Solids content: 55.0 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void

(Contd. on page 6)

Printing date 12.01.2022 Version number 9 (replaces version 8) Revision: 12.01.2022

Trade name: Motip Hardener

(Contd. of page 5)

· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable	
gases in contact with water	Void

gases in contact with water Void
Oxidising liquids Void
Oxidising solids Void

· Organic peroxides Heating may cause a fire.

Corrosive to metalsDesensitised explosivesVoid

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

GB

Printing date 12.01.2022 Version number 9 (replaces version 8) Revision: 12.01.2022

Trade name: Motip Hardener

(Contd. of page 6)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations. Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN3108	
· 14.2 UN proper shipping name · ADR · IMDG, IATA	3108 ORGANIC PEROXIDE TYPE E, SOLID (diber peroxide), ENVIRONMENTALLY HAZARDOUS ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)	
· 14.3 Transport hazard class(es)	регохиче)	
· ADR		
· Class	5.2 (P1) Organic peroxides. 5.2	
· IMDG, IATA	5.2 Organic peroxides.	
· Class · Label	5.2 Organic peroxiaes. 5.2	
· 14.4 Packing group · ADR, IMDG, IATA	not regulated	
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR):	Yes Symbol (fish and tree)	
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category · Stowage Code · Segregation Code	Warning: Organic peroxides. F-J,S-R D SW1 Protected from sources of heat. SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis. SG72 See 7.2.6.3.2.	

(Contd. on page 8)

Printing date 12.01.2022 Version number 9 (replaces version 8) Revision: 12.01.2022

Trade name: Motip Hardener

	(Contd. of page 7
· Transport/Additional information:	
· <i>ADR</i>	
· Limited quantities (LQ)	500 g
\cdot Excepted quantities (\widetilde{EQ})	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	500 g
\cdot Excepted quantities $(\widetilde{E}Q)$	Code: E0
2	Not permitted as Excepted Quantity
UN ''Model Regulation'':	UN 3108 ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE), 5.2, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E1 Hazardous to the Aquatic Environment

- Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H241 Heating may cause a fire or explosion.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)

Version number 9 (replaces version 8) Revision: 12.01.2022 Printing date 12.01.2022

Trade name: Motip Hardener

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Org. Perox. B: Organic peroxides – Type B Org. Perox. E: Organic peroxides – Type E/F

Acute Tox. 4: Acute toxicity - Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

 $Aquatic\ Acute\ 1:\ Hazardous\ to\ the\ aquatic\ environment\ -\ acute\ aquatic\ hazard\ -\ Category\ 1$ Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

* * Data compared to the previous version altered.

(Contd. of page 8)