

Printing date 02.02.2022 Version number 28 Revision: 31.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: PS Poly-Pox Harder 355

· Article number: P324-00000

· UFI: WF30-U01R-T005-4K47

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment,

services, craftsmen)

SU19 Building and construction work

· Process category PROC19 Manual activities involving hand contact

Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article

ERC8c Widespread use leading to inclusion into/onto article (indoor) ERC8f Widespread use leading to inclusion into/onto article (outdoor)

· Article category AC13 Plastic articles

· Application of the substance / the

mixture

See our technical datasheet for application details of this product.

Epoxy curing agent

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Poly-Service BV, Hoogeveenenweg 83, NL 2913 LV Nieuwerkerk a/d IJssel

Tel: +31 180 314777, Fax: +31 180 317847

E-mail: info@polyservice.nl

· Further information obtainable

110111.

Research and Development.


· 1.4 Emergency telephone

number: Poly-Service BV, Tel: +31 180 314777, E-mail: info@polyservice.nl

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



Repr. 2 H361d Suspected of damaging the unborn child.

GHS05 corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

<!> GHS07

Acute Tox. 4 H302 Harmful if swallowed. Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

· Labelling according to Regulation

(EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

· Hazard pictograms

GHS05 GHS07 GHS08 GHS09

· Signal word Danger

· Hazard-determining components of

labelling: 3-aminomethyl-3,5,5-trimethylcyclohexylamine

m-phenylenebis(methylamine)

Salicylic acid Benzyl alcohol phenol, styrenated Phenol, methylstyrenated

· Hazard statements H302+H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage.

(Contd. on page 2)



Printing date 02.02.2022 Version number 28 Revision: 31.01.2022

Trade name: PS Poly-Pox Harder 355

(Contd. of page 1)

H317 May cause an allergic skin reaction.
 H361d Suspected of damaging the unborn child.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/

national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

⋅ PBT: Not applicable.⋅ vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	25 – 50%	
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	10 – 25%	
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50	m-phenylenebis(methylamine) Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10 – 25%	
CAS: 68609-08-5 EC number: 614-657-1	Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-,reaction products with bisphenol A diglycidyl ether homopolymer Skin Corr. 1B, H314; Eye Dam. 1, H318	10 – 25%	
CAS: 69-72-7 EINECS: 200-712-3 Reg.nr.: 01-2119486984-17	Salicylic acid ❖ Repr. 2, H361d; ❖ Eye Dam. 1, H318; ❖ Acute Tox. 4, H302	2.5 – 10%	
CAS: 61788-44-1 EINECS: 262-975-0 Reg.nr.: 01-2119980970-27	phenol, styrenated Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5 – 10%	
CAS: 68512-30-1 EINECS: 270-966-8 Reg.nr.: 01-2119555274-38	Phenol, methylstyrenated Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	2.5 – 10%	
CAS: 112-53-8 EINECS: 203-982-0 Reg.nr.: 01-2119485976-15	Lauryl alcohol Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Eye Irrit. 2, H319	0.5 – 1%	
CAS: 61788-46-3 EINECS: 262-977-1 Index number: 612-285-00-4 Reg.nr.: 01-2119473798-17	Amines, coco alkyl ❖ STOT RE 2, H373; Asp. Tox. 1, H304; ❖ Skin Corr. 1B, H314; Eye Dam. 1, H318; ❖ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); ❖ Acute Tox. 4, H302; STOT SE 3, H335	0.5 – 1%	
· Additional information:	For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical

observation for at least 48 hours after the accident.

(Contd. on page 3)



Printing date 02.02.2022 Version number 28 Revision: 31.01.2022

Trade name: PS Poly-Pox Harder 355

(Contd. of page 2)

· After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing: Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

 4.2 Most important symptoms and effects, both acute and

delayed
- 4.3 Indication of any immediate

No further relevant information available.

4.3 Indication of any immediate medical attention and special

treatment needed No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from

the substance or mixture During heating or in case of fire poisonous gases are produced.

· 5.3 Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and

emergency procedures Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away. **6.2 Environmental precautions:**Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders,

sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

 \cdot Information about fire - and

explosion protection: Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

No special requirements.

· Information about storage in one common storage facility:

Not required.

· Further information about storage

conditions:

Keep container tightly sealed.

· Recommended storage

5 - 30 🗆

temperature: 7.3 Specific end use(s)

No further relevant information available.

(Contd. on page 4)



Printing date 02.02.2022 Version number 28 Revision: 31.01.2022

Trade name: PS Poly-Pox Harder 355

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Additional information about design of technical facilities:

No further data; see item 7.

· Ingredients with limit values that require monitoring at the

require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

	have to be monitored at the workplace.			
· DNEL (De	rived No Effect Level) for workers			
2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine				
Inhalative	Acute - systemic effects, worker	0.073 mg/m	า³ (Worker)	
	Acute - local effects, worker	20.1 mg/m ³	³ (Worker)	
100-51-6 I	Benzyl alcohol	Į.		
Dermal	Long-term - systemic effects, worker	8 mg/kg bw	ı/day (Worker)	
Inhalative	Long-term - systemic effects, worker	22 mg/m³ (\	Worker)	
1477-55-0	m-phenylenebis(methylamine)	l .		
Dermal	Long-term - systemic effects, worker	0.33 mg/kg	bw/day (Worker)	
Inhalative	Long-term - systemic effects, worker	1.2 mg/m³ ((Worker)	
68609-08-	5 Cyclohexanemethanamine, 5-ami homopolymer	no-1,3,3-trir	methyl-,reaction products with bisphenol A diglycidyl e	ther
Dermal	Long-term - systemic effects, worker	560 mg/kg	bw/day (Worker)	
Inhalative	Acute - local effects, worker	9.87 mg/m ³	(Worker)	
	Long-term - systemic effects, worker	247 mg/m ³	(Worker)	
69-72-7 Sa	alicylic acid	<u> </u>		
Dermal	Long-term - systemic effects, worker	2.3 mg/kg b	ow/day (Worker)	
Inhalative	Long-term - systemic effects, worker	5 mg/m³ (W	/orker)	
61788-44-	1 phenol, styrenated			
Dermal	Long-term - systemic effects, worker	3.5 mg/kg b	ow/day (Worker)	
Inhalative	Long-term - systemic effects, worker	7.4 mg/m³ ((Worker)	
	1 Phenol, methylstyrenated	•		
Dermal	Long-term - systemic effects, worker	3.5 mg/kg b	ow/day (Worker)	
Inhalative	Long-term - systemic effects, worker	1.4 mg/m³ ((Worker)	
112-53-8 I	Lauryl alcohol	•		
Dermal	Long-term - systemic effects, worker	125 mg/kg	bw/day (Worker)	
Inhalative	Long-term - systemic effects, worker	220 mg/m ³	(Worker)	
	3 Amines, coco alkyl			
Dermal	Long-term - systemic effects, worker	0.09 mg/kg	bw/day (Worker)	
Inhalative	Long-term - systemic effects, worker	0.38 mg/m ³	(Worker)	
· DNEL (De	rived No Effect Level) for the general	population		
1	3-aminomethyl-3,5,5-trimethylcyclo	•		
Oral	Long-term - systemic effects, general	l population	0.526 mg/kg bw/day (General population)	
100-51-6 I	Benzyl alcohol			
Oral	Long-term - systemic effects, general	l population	4 mg/kg bw/day (General population)	
	1		4 mg/kg bw/day (General population)	
Inhalative	Long-term - systemic effects, general	l population	5.4 mg/m³ (General population)	
68609-08-	68609-08-5 Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-,reaction products with bisphenol A diglycidyl ether homopolymer			ther
Oral	Acute - systemic effects, general pop	ulation	0.99 mg/kg bw/day (General population)	
			0.33 mg/kg bw/day (General population)	
Dermal	1		0.67 mg/kg bw/day (General population)	
Inhalative	Acute - systemic effects, general pop		1.74 mg/m³ (General population)	
	Long-term - systemic effects, general		87 mg/m³ (General population)	
			I	



Version number 28 Revision: 31.01.2022 Printing date 02.02.2022

Trade name: PS Poly-Pox Harder 355

	(Contd. of page	
69-72-7 Salicylic acid	, , ,	
1	oppulation 1 mg/kg bw/day (General population)	
	oppulation 1 mg/kg bw/day (General population)	
Inhalative Long-term - systemic effects, general p	oppulation 4 mg/m³ (General population)	
· PNEC (Predicted No Effect Concentration) values		
2855-13-2 3-aminomethyl-3,5,5-trimethylcycloh	exylamine	
Aquatic compartment - freshwater	0.06 mg/l (Freshwater)	
Aquatic compartment - marine water	0.006 mg/l (Marine water)	
Aquatic compartment - water, intermittent releases	s 0.23 mg/l (Intermittent release water)	
Aquatic compartment - sediment in freshwater	5.784 mg/kg sed dw (Sediment freshwater)	
Aquatic compartment - sediment in marine water	0.578 mg/kg sed dw (Sediment marine water)	
Terrestrial compartment - soil	1.121 mg/kg dw (Soil)	
Sewage treatment plant	3.18 mg/l (stp)	
100-51-6 Benzyl alcohol		
Aquatic compartment - freshwater	1 mg/l (Freshwater)	
Aquatic compartment - marine water	0.1 mg/l (Marine water)	
1477-55-0 m-phenylenebis(methylamine)		
Aquatic compartment - freshwater	0.094 mg/l (Freshwater)	
Aquatic compartment - marine water	0.0094 mg/l (Marine water)	
Aquatic compartment - water, intermittent releases	s 0.152 mg/l (Intermittent release water)	
Aquatic compartment - sediment in freshwater	0.43 mg/kg sed dw (Sediment freshwater)	
Aquatic compartment - sediment in marine water	0.043 mg/kg sed dw (Sediment marine water)	
Terrestrial compartment - soil	0.045 mg/kg dw (Soil)	
Sewage treatment plant	10 mg/l (stp)	
68609-08-5 Cyclohexanemethanamine, 5-amino homopolymer	p-1,3,3-trimethyl-,reaction products with bisphenol A diglycidyl ether	
Aquatic compartment - freshwater	0.002 mg/l (Freshwater)	
Aquatic compartment - marine water	0 mg/l (Marine water)	
Aquatic compartment - sediment in freshwater	10.5 mg/kg sed dw (Sediment freshwater)	
Aquatic compartment - sediment in marine water	1.05 mg/kg sed dw (Sediment marine water)	
Terrestrial compartment - soil	2.1 mg/kg dw (Soil)	
Sewage treatment plant	3.1 mg/l (stp)	
69-72-7 Salicylic acid		
Aquatic compartment - freshwater	0.2 mg/l (Freshwater)	
Aquatic compartment - marine water	0.02 mg/l (Marine water)	
61788-44-1 phenol, styrenated		
Aquatic compartment - freshwater	0.03 mg/l (Freshwater)	
Aquatic compartment - marine water	0.003 mg/l (Marine water)	
68512-30-1 Phenol, methylstyrenated	•	
Aquatic compartment - freshwater	0.014 mg/l (Freshwater)	
Aquatic compartment - marine water	0.0014 mg/l (Marine water)	
112-53-8 Lauryl alcohol	•	
Aquatic compartment - freshwater	0.0028 mg/l (Freshwater)	
Aquatic compartment - marine water	0.00028 mg/l (Marine water)	
61788-46-3 Amines, coco alkyl	•	
Aquatic compartment - freshwater	0.00026 mg/l (Freshwater)	
Aquatic compartment - marine water	0.000026 mg/l (Marine water)	
. Additional information: The lists valid		

· Additional information:

The lists valid during the making were used as basis.

- · **8.2 Exposure controls** · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.



Version number 28 Revision: 31.01.2022 Printing date 02.02.2022

Trade name: PS Poly-Pox Harder 355

(Contd. of page 5)

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

In case of brief exposure or low pollution use respiratory filter device. In case of · Respiratory protection:

intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands: Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/

the preparation.

Due to missing tests no recommendation to the glove material can be given for the

product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of

diffusion and the degradation

· Material of gloves Nitrile rubber, NBR

> The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.3 mm

· Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective

gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least

480 minutes (Permeation according to EN 16523-1:2015: Level 6).

· For the permanent contact gloves made of the following materials are

Nitrile rubber, NBR

· As protection from splashes gloves made of the following materials are suitable:

Not suitable are gloves made of

Nitrile rubber, NBR

the following materials:

Leather gloves Strong material gloves

· Eye protection: Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1	Information	on basic p	hysical and	l chemica	l properties

· General Information

· Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined.

· pH-value at 20 °C:

9.5

· Change in condition

· Flammability (solid, gas):

· Decomposition temperature:

· Vapour pressure at 20 °C:

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 205 °C

· Flash point: 101 °C (Pensky Martens, ASTM D93)

435 °C

· Ignition temperature:

· Auto-ignition temperature: Product is not selfigniting.

Product does not present an explosion hazard. Explosive properties:

0.1 hPa

Not applicable.

Not determined.

· Explosion limits:

Lower: 1.3 Vol % 13 Vol % Upper:

· Density at 20 °C: 1.02 g/cm3 (DIN 51757, ASTM D 1298)

· Relative density Not determined. · Vapour density Not determined.

(Contd. on page 7)



Printing date 02.02.2022 Version number 28 Revision: 31.01.2022

Trade name: PS Poly-Pox Harder 355

(Contd. of page 6)

	(Conta. or page o)
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic at 20 °C: Kinematic:	600 mPas (Brookfield, ASTM D1544) Not determined.
· Solvent content: Organic solvents: VOC (2004/42/EC):	15.0 % 15.00 %
Solids content:	100.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

10.2 Chemical stability
 Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous

reactions No dangerous reactions known.

10.4 Conditions to avoid
 10.5 Incompatible materials:
 No further relevant information available.
 No further relevant information available.

· 10.6 Hazardous decomposition

products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Harmful if swallowed or if inhaled.

· LD/LC50 values relevant for classification:

· Components	Туре	Value	Species	
ATE (Acute Toxicit	y Estimates)			
Oral LD50 904 r	ng/kg			
Dermal LD50 2,933	3 mg/kg			
100-51-6 Benzyl ald	cohol			

Dermal	Dermal LD50 2,933 mg/kg				
100-51-	100-51-6 Benzyl alcohol				
Oral	LD50	1,230 mg/kg (Rat)			
Dermal	LD50	2,000 mg/kg (Rabbit)			
1477-55	1477-55-0 m-phenylenebis(methylamine)				
Oral	Oral LD50 1,040 mg/kg (Rat)				
69-72-7	69-72-7 Salicylic acid				
Oral	Oral LD50 891 mg/kg (Rat)				
	112-53-8 Lauryl alcohol				
Oral	Oral LD50 12,800 mg/kg (Rat)				
Duine	- Drimony irritant affect:				

· Primary irritant effect:

· Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/irritation
 Respiratory or skin sensitisation
 Causes serious eye damage.
 May cause an allergic skin reaction.

· Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Suspected of damaging the unborn child.

• STOT-single exposure
• STOT-repeated exposure
• Aspiration hazard

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

(Contd. on page 8)



Printing date 02.02.2022 Version number 28 Revision: 31.01.2022

Trade name: PS Poly-Pox Harder 355

(Contd. of page 7)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

· Type of test Effective concentration Method Assessment

ATE (Acute Toxicity Estimates)

Inhalative | LC50/4 h | 13.1 mg/l

1477-55-0 m-phenylenebis(methylamine)

Inhalative LC50/4 h 2.4 mg/l (Rat)

· 12.2 Persistence and

degradability
12.3 Bioaccumulative potential
12.4 Mobility in soil
No further relevant information available.
No further relevant information available.
No further relevant information available.

· Ecotoxical effects:

· Remark: Toxic for fish

· Additional ecological information:

General notes: Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for

water

Do not allow product to reach ground water, water course or sewage system, even in

small quantities.

Must not reach sewage water or drainage ditch undiluted or unneutralised. Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· 12.5 Results of PBT and vPvB assessment

⋅ PBT: Not applicable.⋅ vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed together with household garbage. Do not allow product to reach

sewage system.

· European	· European waste catalogue		
	08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS		
08 01 00	3 01 00 wastes from MFSU and removal of paint and varnish		
08 01 11*	1* waste paint and varnish containing organic solvents or other hazardous substances		
HP6	Acute Toxicity		
HP8	Corrosive		
HP10	Toxic for reproduction		
HP13	Sensitising		
HP14	Ecotoxic		

· Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR/RID/ADN, IMDG, IATA	UN1760
· 14.2 UN proper shipping name · ADR/RID/ADN	1760 CORROSIVE LIQUID, N.O.S. (m-
, and the second	phenylenebis(methylamine), ISOPHORONEDIAMINE), ENVIRONMENTALLY HAZARDOUS
· IMDG	CORROSIVE LIQUID, N.O.S. (m-phenylenebis(methylamine), ISOPHORONEDIAMINE), MARINE POLLUTANT

(Contd. on page 9)



Printing date 02.02.2022 Version number 28 Revision: 31.01.2022

Trade name: PS Poly-Pox Harder 355

	(Contd. of page 8)
·IATA	CORROSIVE LIQUID, N.O.S. (m-phenylenebis(methylamine), ISOPHORONEDIAMINE)
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
· Class	8 (C9) Corrosive substances.
·Label	8
· IMDG, IATA	0.00
· Class · Label	8 Corrosive substances.
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	1
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: phenol, styrenated
· Marine pollutant:	Yes
· Special marking (ADR/RID/ADN):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user	,
Hazard identification number (Kemler code):	Warning: Corrosive substances. 88
· EMS Number:	F-A,S-B
· Stowage Category	B SWO Class of living sweeters
· Stowage Code	SW2 Clear of living quarters.
 14.7 Transport in bulk according to Annex II of Mand the IBC Code 	Marpol Not applicable.
44	пот аррисаріе.
· Transport/Additional information:	
· ADR/RID/ADN · Limited quantities (LQ)	0
· Excepted quantities (EQ)	Code: F0
Excepted quantities (EQ)	Not permitted as Excepted Quantity
Transport category	1
· Tunnel restriction code	E
· IMDG	0
Limited quantities (LQ)Excepted quantities (EQ)	0 Code: E0
Excepted quantities (EQ)	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S. (M- PHENYLENEBIS(METHYLAMINE), ISOPHORONEDIAMINE), 8, I, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances -

ANNEX I None of the ingredients is listed.

· Seveso category E2 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the

application of lower-tier

requirements 200 t

· Qualifying quantity (tonnes) for the

application of upper-tier

requirements 500 t

REGULATION (EC) No 1907/2006

ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 10)

(Contd. of page 9)



Safety data sheet according to 1907/2006/EC, Article 31

Version number 28 Revision: 31.01.2022 Printing date 02.02.2022

Trade name: PS Poly-Pox Harder 355

· REGULATION (EU) 2019/1148 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

Technical instructions (air):

Class Share in % NK 15.0

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

 Relevant phrases H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

Regulation (EC) No 1272/2008.

The classification of the mixture is generally based on the

calculation method using substance data according to

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Acute toxicity - oral Acute toxicity - inhalation Skin corrosion/irritation

Serious eye damage/eye irritation

Skin sensitisation Reproductive toxicity

Hazardous to the aquatic environment - long-term (chronic)

aquatic hazard

· Department issuing SDS: Research and Development

· Contact: G. Lok (tel +31 0180 314777, e-mail info@polyservice.nl)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer · Abbreviations and acronyms:

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 11)



Printing date 02.02.2022 Version number 28 Revision: 31.01.2022

Trade name: PS Poly-Pox Harder 355

(Contd. of page 10)

Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· Sources: Literature data and/or investigation reports are available through the manufacturer.

· * Data compared to the previous version altered.